



- NOTES:
- ▽ THIS SYMBOL INDICATES CIRCUIT GROUND.
 - ≡ THIS SYMBOL INDICATES CHASSIS GROUND.
 - THIS SYMBOL INDICATES A DC VOLTAGE MEASUREMENT TO THE -V TERMINAL, UNLESS OTHERWISE SPECIFIED. CIRCUIT CONDITIONS INCLUDE:
 1. NOMINAL LINE VOLTAGE OF 120 VAC (240 VAC).
 2. NO LOAD.
 3. VOLTAGE CONTROLS FULLY CLOCKWISE.
 4. CURRENT CONTROL FULLY CLOCKWISE.
 5. STAND-BY SWITCH TO DC ON.
 - * THIS SYMBOL INDICATES A DC VOLTAGE MEASUREMENT TO THE -V TERMINAL UNDER FULL RATED LOAD CONDITIONS.
 - THIS SYMBOL INDICATES A CIRCUIT BOARD WIRE CONNECTION.
 - ↻ ARROW INDICATES CLOCKWISE ROTATION.
- ALL RESISTORS ARE 1/2-WATT UNLESS MARKED OTHERWISE. RESISTOR VALUES ARE IN OHMS (K=1,000, M=1,000,000).
- ALL CAPACITOR VALUES ARE IN MICROFARADS UNLESS MARKED OTHERWISE.
- CIRCUIT COMPONENT NUMBERS ARE IN THE FOLLOWING GROUPS:
 0-99 CHASSIS MOUNTED PARTS.
 100-199 CIRCUIT BOARD PARTS.

**SCHEMATIC OF THE
HEATHKIT®
60V, 1.5A POWER SUPPLY
MODEL IP-2700**



- NOTES:
- ▽ THIS SYMBOL INDICATES CIRCUIT GROUND.
 - ≡ THIS SYMBOL INDICATES CHASSIS GROUND.
 - THIS SYMBOL INDICATES A DC VOLTAGE MEASUREMENT TO THE -V TERMINAL, UNLESS OTHERWISE SPECIFIED. CIRCUIT CONDITIONS INCLUDE:
 1. NOMINAL LINE VOLTAGE OF 120 VAC (240 VAC).
 2. NO LOAD.
 3. VOLTAGE CONTROLS FULLY CLOCKWISE.
 4. CURRENT CONTROL FULLY CLOCKWISE.
 5. STAND BY SWITCH TO DC ON.
 - * THIS SYMBOL INDICATES A DC VOLTAGE MEASUREMENT TO THE -V TERMINAL UNDER FULL RATED LOAD CONDITION.
 - THIS SYMBOL INDICATES A CIRCUIT BOARD WIRE CONNECTION.



ARROW INDICATES CLOCKWISE ROTATION.


ALL RESISTORS ARE 1/2-WATT UNLESS MARKED OTHERWISE. RESISTOR VALUES ARE IN OHMS (K=1,000, M=1,000,000).

ALL CAPACITOR VALUES ARE IN MICROFARADS UNLESS MARKED OTHERWISE.

CIRCUIT COMPONENT NUMBERS ARE IN THE FOLLOWING GROUPS:

0-99 CHASSIS MOUNTED PARTS.
100-199 CIRCUIT BOARD PARTS.

SCHEMATIC C
HEATHKIT
60V, 1.5A POWER
MODEL IP-5



**SCHEMATIC OF THE
 RATHKIT®
 POWER SUPPLY
 MODEL IP-2700**